


VIDEO SURVEILLANCE solutions



YOUR INTELLIGENT WORLD

GUARDING YOUR HOME, YOUR BUSINESS AND HELPING YOU MAKE DATA DRIVEN DECISIONS.

AT THE HEART OF ANY CONNECTED TECHNOLOGY LIES A HUMAN EXPERIENCE. INNOVATIVE AND INSPIRED THINKING IS WHAT THE FOUNDATION OF OZAAS IS BUILT ON. OUR INNOVATION RADAR IS CONSISTENTLY DRIVEN BY OUR AMBITION TO HELP THE WORLD LIVE SMARTER, WITH PRODUCTS THAT PROMISE COMFORT AND PEACE OF MIND.

ozaas AHD CAMERAS



1MP IR AHD Bullet Camera



Features

- 1/1.4" 1.0MP CMOS
- 3.6mm Fixed Lens
- Up to 20m IR distance
- 4 IN1 AHD/CVI/TVI/CVBS
- UTC & OSD support
- IP66 weatherproof
- Night Vision



OZ-V1-AMBH20-300 2MP IR Bullet HD Camera



Features

- 1/2.7" 2.0MP CMOS
- 3.6mm Lens
- Up to 20m IR distance
- 4 IN1 AHD/CVI/TVI/CVBS
- IP66 weatherproof
- UTC & OSD support
- Night Vision




OZ-V1-AEDH10-200 1MP IR AHD Dome Camera



Features

- 1/4" 1.0MP CMOS
- 3.6mm Fixed Lens
- Up to 20m IR distance
- 4 IN1 AHD/CVI/TVI/CVBS
- UTC & OSD support
- Night Vision



20m IR Distance

OZ-V1-AMDH20-300 2MP IR Dome HD Camera

2MP IR Dome HD Camera



Features

- 1/2.7" 2.0MP CMOS
- 3.6mm Lens
- Up to 20m IR distance
- 4 IN1 AHD/CVI/TVI/CVBS
- IP66 weatherproof
- UTC & OSD support
- Night Vision



OZAAS XVR RECORDERS

TAAS

Ozaas XVRs can recieve video transmission from multiple HD Analog cameras located in local or remote sites. Each recorder can be fitted with 6TB SATA disks with up to 12TB in capacity, and stores recordings from multiple cameras using motion JPEG, MPEG-4 or H.264 streaming technology.



Features

- Analog / AHD / CVI / TVI / IP cam compatible
- Up to HD 1080N & IP 5MP Res Recording
- HDMI, VGA and CVBS Video Output
- Supports 16CH HD or 16CH IP Camera Input
- 2 SATA HDD (Upto 12TB capacity)
- Smartphone Remote Monitoring

OZ-V1-AMX8A0H-UK/EU 8CH XVR 5IN1 H.264



Features

- Analog / AHD / CVI / TVI / IP cam compatible
- Recording Res up to HD 1080N and IP 1080P
- HDMI, VGA and CVBS Video Output
- Supports 8CH HD or 16CH IP Camera Input
- 1 SATA HDD (Upto 6TB capacity)
- Smartphone Remote Monitoring

OZAAS

ozaas IP CAMERAS

OZ-V1-APBN40-400

4MP IR Bullet HD IP Camera



Features

- 1/3"OV Hi-Res CMOS
- 6mm Fixed Lens
- Up to 40m IR distance
- H.264/H.265 compression
- IP66, PoE
- Night Vision



OZ-V1-APBN40-405 4MP IR Bullet HD 5X IP Camera



Features

- 1/3"OV Hi-Res CMOS
- 2.7-13.5mm 5X Motor Zoom
- Up to 40m IR distance
- H.264/H.265 compression
- IP66, PoE
- Night Vision



OZ-V1-APDN40-400 4MP IR Dome HD IP Camera



Features

- 1/3"OV Hi-Res CMOS
- 3.6mm Fixed Lens
- Up to 20m IR distance
- H.264/H.265 compression
- IP66, PoE
- Night Vision



OZ-V1-APDN40-405 4MP IR Dome HD 5X IP Camera

Features

- 1/3"OV Hi-Res CMOS
- 2.7-13.5mm 5X Motor Zoom
- Up to 30m IR distance
- H.264/H.265 compression
- IP66, PoE
- Night Vision



OZAAS **NVR RECORDERS**

Ozaas NVRs records 4K, ultra high definition footage on 16 channels. It has 1 SATA interface for HDD storage and 8 power over ethernet (PoE+) ports. The 4K NVR is exactly what you need for recording the highest resolution footage possible.

OZ-V1-APN16A0N1-UK/EU 4K 9 PORT16CH NVR, POE H.265



Features

- 16-channel HD NVR with 4K capability
- Compatible with any IP camera
- Up to 8MP Res Recording & Playback
- HDMI & VGA Output
- H.265/H.264 Video Forma
- 1 SATA HDD (Upto 6TB capacity)
- Supports 8 PoE Network Interfaces
- Smartphone Remote Monitoring

OZ-V1-APN8A0N1-UK/EU 4K 8CH NVR, POE H.265



Features

- 8-channel HD NVR with 4K capability
- Compatible with any IP camera
- Up to 8MP Res Recording & Playback
- HDMI & VGA Output
- H.264/H.265 Video Format
- 1 SATA HDD (Upto 6TB capacity)
- Smartphone Remote Monitoring





ozaas FISH EYE IP CAMERA

OZ-V1-FPDN40-600

4MP Panoramic IR Fisheye IP Camera



Features

- 1/2.9"SONY Low Illumination CMOS
- 1.05mm Panoramic Lens/ 5MP Res
- H.265/H.264 Compression
- Up to 20m IR distance
- SD Card Slot (Max. 64GB)
- PoE (IEEE 802.3af)
- WiFi distance of up to 300m
- Two-Way Audio
- Alarm In/Out, CVBS

Additional Functionalities to Optimize your premises



Smartphone Monitoring --Real-time monitoring - Event alarm detection

Image: Day/Night Image: Day/Night Image: Day POE Image: Day/Night Image: Day Image: Day POE Image: Day Imag

2-way Audio e-PTZ



OZAAS NVR RECORDERS

OZAAS

Support fisheye video de-warping in local and web user interface. Select from our 8ch or 16ch NVR depending on your preferred number of display splits.



Compression

Lщ

Defog Mode





5MP IMAGE CLARITY 6

DRAGE 2-WAY









A 360° SOLUTION FOR ANY BUSINESS

Retail stores, offices or homes need minimum installation with minmum maintenance. Ozaas panaromic fisheye camera is a perfect solution.



fisheye Minimum 4 cameras required Just one camera needed



ozaas Wi-Fi CAMERA KIT

OZ-V1-WEBH10-300 1MP 4CH WiFi Kit 300m distance

1 x 4CH Wi-Fi NVR H.264



Features

- Wi-Fi NVR with 5dBi Antenna
- Wi-Fi Transmission upto 300m (Subject to no obstructions)
- Video Compression: H.264
- HDMI & VGA Output
- Better heat dispersion



4 x 1MP Outdoor Bullet IP





- 1/4" 1.0MP CMOS Sensor
- 3.6mm Lens
- Up to 25m IR distance
- Privacy Masking
- IP66 Weatherproof



4 x DC12V/0.5A Power



1 x DC12V/2A Power Adapter for WIFI NVR



EVERYTHING YOU NEED TO START BUILDING YOUR HOME SECURITY

Easy to use HD WiFi camera kit helps you monitor your home or business from anywhere with your laptop, tablet or smartphone. No matter where you are, you're always home.



EASY INSTALLATION

Ozaas Wifi surveillance kit is designed for easy installation and simple plug and play. Ozaas Wi-Fi kit come with a short and simple installation. Now you can have total peace of mind and more time for what matters.



PRIVACY MASKING

Protect personal privacy by concealing parts of the image from view with a masked area.



REMOTE VIEWING FROM YOUR SMARTPHONE

Share the Action - Easily share camera access, or specific videos, with friends and family so everyone's caught up on the latest events.



OZAAS VIDEO MANAGEMENT SOLUTION (VMS)




Ozaas Video Management System (VMS) is a powerful, reliable and scalable solution for video surveillance and business management. It can be deployed in small projects containing only few cameras as well as large installations with hundreds of cameras, access control and other devices.

Ozaas VMS Pro is designed for large projects to provide Video Monitoring, Recording Setting and access to facility maps and alarms. It also can provide flexible and diverse deployment plans to meet the demands of medium or small projects in varieties of different environments.



VIDEO ANALYTICS

OZAAS will soon launch industry defining technologies - OZAAS CLOUD and OZAAS ANALYTICS, which will turn the standard surveillance system to one that is connected to the cloud and provides storage and world class video analytics in easy and affordable ways. OZAAS Video analytics will have several features to enhance security based on face recognition, entry/exit as well as the periphery security.



AHD CAMERAS

| | AHD CAMERAS | | | | |
|--------------------------|---|--------------------------------------|--------------------------------------|--------------------------------------|--|
| | OZ-V1-AEBH10-200 | OZ-V1-AEDH10-200 | OZ-V1-AMDH20-300 | | |
| MODEL | 1MP Bullet AHD Camera | 1MP Dome AHD Camera | 2MP Bullet AHD Camera | 2MP Dome AHD Camera | |
| | 0 | | 1 | 0 | |
| Image Sensor | 1/4" 1MP CMOS | 1/4" 1MP CMOS | 1/2.7" 2MP CMOS | 1/2.7" 2MP CMOS | |
| Image Resolution | 1MP 720P/ 960H | 1MP 720P/ 960H | 2MP 1080P/ 960H | 2MP 1080P/ 960H | |
| Effective Pixels | 1280*720 | 1280*720 | 1920*1080 | 1920*1080 | |
| TV System | PAL/NTSC | PAL/NTSC | PAL/NTSC | PAL/NTSC | |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s | 1/25s~1/50,000s , 1/30s~1/60,000s | 1/25s~1/50,000s , 1/30s~1/60,000s | 1/25s~1/50,000s , 1/30s~1/60,000s | |
| S/N Ratio | ≥50dB | ≥50dB | ≥50dB | ≥50dB | |
| Scanning System | Progressive Scan | Progressive Scan | Progressive Scan | Progressive Scan | |
| Focus Length | 3.6mm | 3.6mm | 3.6mm | 3.6mm | |
| Focus Control | Fixed | Fixed | Fixed | Fixed | |
| Lens Type | Fixed | Fixed | Fixed | Fixed | |
| Pixels | 2M Pixels | 2M Pixels | 3M Pixels | 3M Pixels | |
| Infrared LED | 14µ x 18PCS | 14µ x 18PCS | 14µ x 18PCS | 14µ x 18PCS | |
| Infrared Distance | 20M | 20M | 20M | 20M | |
| IR Status | Under 10 Lux by CDS | Under 10 Lux by CDS | Under 10 Lux by CDS | Under 10 Lux by CDS | |
| IR Power On | CDS Auto Control | CDS Auto Control | CDS Auto Control | CDS Auto Control | |
| Day/Night | YES | YES | YES | YES | |
| OSD Menu | YES | YES | YES | YES | |
| Noise Reduction | DNR | DNR | DNR | DNR | |
| Pic Adjustment | YES | YES | YES | YES | |
| WDR | YES | YES | YES | YES | |
| OSD Support | YES | YES | YES | YES | |
| UTC | YES | YES | YES | YES | |
| Housing | Plastic, IP66 | Plastic | Plastic, IP66 | Metal, IP66 | |
| Operation Temperature | -10°C~+50°C | -10°C∼+50°C | -10°C~+50°C | -10°C~+50°C | |
| Power Source | DC12V±10%, 550mA DC12V±10%, 550mA DC12V±10%, 550mA DC12V±10%, 550mA | | | | |

IP CAMERAS

| | IP CAMERAS | | | | |
|-------------------|---|---|---|---|---|
| Model | OZ-V1-APBN 40-400 4MP Bullet IP Camera | OZ-V1-APDN 40-400 4MP Dome IP Camera | OZ-V1-APBN 40-405 4MP Bullet IP 5X AF Camera | OZ-V1-APDN 40-405 4MP Dome IP 5X AF Camera | OZ-V1-FPDN 40-600 4MP Fisheye Camera |
| | 0 | 0 | 0- | 0 | ۲ |
| Image Sensor | 1/3" OV Hi-Res CMOS | 1/3" OV Hi-Res CMOS | 1/3" OV Hi-Res CMOS | 1/3" OV Hi-Res CMOS | 1/2.9" SONY Low Illum CMOS |
| Resolution | 4MP | 4MP | 4MP | 4MP | 4MP |
| Effective Pixels | 2688(H)*1520(V) | 2688(H)*1520(V) | 2688(H)*1520(V) | 2688(H)*1520(V) | 3096 (H)*2202(V) |
| Compression | H.264/H.265 | H.264/H.265 | H.264/H.265 | H.264/H.265 | H.264/H.265 |
| TV System | PAL/NTSC | PAL/NTSC | PAL/NTSC | PAL/NTSC | PAL/NTSC |
| S/N Ratio | ≥52dB | ≥52dB | ≥52dB | ≥52dB | ≥52dB |
| Video Output | Network | Network | Network | Network | Network, cvbs |
| Focus Length | 6mm | 3.6mm | 2.7-13.5mm | 2.7-13.5mm | 1.05mm |
| Focus Control | Fixed | Fixed | Auto | Auto | Fixed |
| Lens Type | Fixed | Fixed | Motorized | Motorized | Fixed |
| Pixels | 4MP | 4MP | 5MP | 5MP | 5MP |
| Infrared LED | 42µ x 4PCS | 14µ x 18PCS | 42µ x 4PCS | 14µ x 24PCS | 42µx 3PCS |
| Infrared Distance | 40M | 20M | 40M | 30M | 20M |
| P2P | YES, QR Code | YES, QR Code | YES, QR Code | YES, QR Code | YES, QR Code |
| POE | Support | Support | Support | Support | Support |
| Day/Night | Yes | Yes | Yes | Yes | Yes |
| Defog Mode | Support | Support | Support | Support | Support |
| WDR | Support | Support | Support | Support | Support |
| Motion Detection | Support | Support | Support | Support | Support |
| Privacy Masking | Support | Support | Support | Support | Support |
| SD Card Slot | Yes, Max 64GB | Yes, Max 64GB | Yes, Max 64GB | Yes, Max 64GB | Yes, Max 64GB |
| Housing | Plastic ,IP66 | Metal IP66 | Plastic ,IP66 | Metal IP66 | Metal |
| Operation Temp | -20°C~+60°C | -20°C~+60°C | -20°C~+60°C | -20 °C $\sim +60$ °C | -20°C ~ +60°C |
| Power Source | DC12V±10%, 1000mA | DC12V±10%, 850mA | DC12V±10%, 1000mA | DC12V±10%, 1000mA | DC12V±10%, 950mA |

XVR RECORDERS

07-V1-AMX8A0H-UK/FU

8CH H.264 5IN1 XVR 1080N

XVR RECORDERS

OZ-V1-APX-16A0H2-UK/EU 16CH H.264 5IN1 XVR 1080N

16CH BNC Analog/AHD/CVI/TVI 2.0/Network 1 VGA, 1CVBS,1 HDMI 16 Channel Recording, Alarm, Email, Buzzer RS485 16 Channel/9 Channel/8 Channel /4 Channel / 1Channel 1 Rectangular Zones Camera title, Time, Motion detection, Recording H.264 G711u Manual\Timer\Motion Detection

4CH 1080P@30fps 4 Channel / 1 Channel 1 RJ45 10M/100M/1000M iPhone, ipad, Android ,Android pad 2 SATA Interface 2 SATA Hard Disk (Up to 12TB) English YES 2 USB 2.0 Interfaces DC 12V \leq 10W (Without Hard Disk) -10~55°C/10~90% 8CH BNC Analog/AHD/CVI/TVI 2.0/Network 1HDMI,1 VGA, 1CVBS 8 Channel Recording, Alarm, Email, Buzzer RS485 16 Channel/9 Channel/8 Channel /4 Channel / 1Channel 1 Rectangular Zones Camera title, Time, Video loss Motion detection, Recording H.264 G711u Manual\Timer\Motion Detection

4CH 1080P@30fps 4 Channel / 1 Channel 1 RI45 10M/100M/1000M

iPhone, ipad, Android ,Android pad 1 SATA Interface 1 SATA Hard Disk (Up to 6TB) English YES 2 USB 2.0 Interfaces DC 12V ≤6W (Without Hard Disk) -10~55°C/10~90%

Model

Input Signal Type Output Motion Detection **Trigger Events** Interface **Display Split** Privacy Masking OSD Video Compression Audio Compression Record Mode Decode Capability Remote Playback Network Interface Smart Phone HD Interface HD Capacity Language UTC Control USB Interface Power consumption Working Environment

NVR RECORDERS

| | NVR RECORDERS | | | |
|----------------------|--|--|--|--|
| | OZ-V1-APN8A0N1-UK/EU | OZ-V1-APN16A0N1-UK/EU | | |
| | 8CH.H.265 POE NVR 4K | 9PORT, 16CH H.265 POE NVR 4K | | |
| Model | | | | |
| Input | 8CH | 16CH | | |
| Output | 1 VGA, 1 HDMI | 1 VGA, 1 HDMI | | |
| Audio Bit Rate | 64kbps | 64kbps | | |
| Audio Compression | G.711 | G.711 | | |
| Motion Detection | 8 Channel | 16 Channel | | |
| Trigger Events | Recording, Email, FTP, Snapshot, Buzzer and ScreenTips, alarm output 8CHxD1/4CHxD1/1CHx1080P/1CHx3MP | Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output | | |
| Display Split | /1CHx4MP/1CHx5MP/1CHx4k | 9CHxD1/4CHxD1/1CHx1080P/1CHx3MP /1CHx4MP/1CHx5MP/1CHx4k | | |
| Digital Zoom | YES | YES | | |
| OSD | Camera Title, Time, Video Loss, Recording Motion Detection | Camera Title, Time, Video Loss, Recording, Motion Detection | | |
| Video Compression | H.264/H.265 | H.264/H.265 | | |
| Decode Capability | 1CH 4K(3840×2160)@30fps | 1CH 4K(3840×2160)@30fps | | |
| Remote Sync Playback | YES | YES | | |
| Interface | 1 x RJ45 (10M/100M Adaptive Ethernet) | 9 x RJ45 (10M/100M Adaptive Ethernet) | | |
| Incoming Bandwidth | 80MB | 80MB | | |
| Onvif Version | Support Onvif 2.4 | Support Onvif 2.4 | | |
| Cloud Support(P2P) | Yes | Yes | | |
| Smart Phone | iPhone, iPad, Android, Android Pad | iPhone, iPad, Android, Android Pad | | |
| Storage Interface | 1 SATA Interface | 1 SATA Interface | | |
| Storage Capacity | Up to 6TB capacity | Up to 6TB capacity | | |
| Language | English | English | | |
| USB Interface | 2 USB 2.0 Interfaces | 2 USB 2.0 Interfaces | | |
| Power Supply | DC12V/2A | DC48V/2500mA ≤10W | | |
| Working Environment | -10~55° C /10~90% | -10~55° C /10~90% | | |



Distributed by

* Design and specifications are subject to change without notice.

Ozaas® 2018 All Rights Reserved